

Digital temperature display

Minimum/maximum temperature memory

Visual and audible alarm signal, even in the case of power failure

Key switch

Forced-air cooling

Comfortable access

3 drawers with cover plate

Automatic fast defrosting

Connection for forwarding alarms and for PC-supported temperature documentation

Condensate evaporation



The KIRSCH-PC-KIT

In conjunction with the software KIRSCH DATANET allows a consistently documentation, including real-time monitoring of your refrigerators and freezers from the PC.




Storage temperature -41 °C

The powerful cooling machine keeps the temperature safe at -41 °C.

FROSTER- BL-180

according to DIN 58375



- **External housing** made from galvanised sheet steel (rust-proof), with white, anti-scratch powder coating. Length of the plug cable: approx. 1.8 m.
- **Adjustable feet** to compensate for uneven floors.
- **Interior made** from smooth aluminium with colourless protective coating.
- **Interior consists** of three drawers of stainless steel with stops, with cover plate on telescopic runners. Capacity per drawer approx. 30 plasma cartons (each 19 x 13 x 2,5 cm), each 400 ml size.
- **Extra-thick 70-mm insulation**, made from high-quality, compression-moulded and environmentally friendly material. Energy saving.
- **Self-closing door** with easy-to-replace plastic magnetic seal frame, lockable.
- **Door stop** on the right-hand side (by default, see illustration), or the left-hand side, can be retrofitted.
- **Forced-air cooling** with axial blower, switches off automatically when you open the door, ensures a uniform temperature and minimises temperature deviations.
- **Automatic fast defrosting** thanks to time-limited and temperature-monitored reversal of the refrigerant circuit.
- **Condensate evaporates** in stainless steel heated dish beneath the refrigerator floor.
- **Key switch protected control panel against tampering.** Membrane keyboard with digital temperature display and minimum/maximum temperature memory.
- **Warning functions** with visual and audible alarm signal in the case of power failure. In the case of power failure, the monitoring unit remains in operation for approx. 72 hours on battery power.
- **Alarms** can be forwarded using the potential-free contact (e.g., to a mobile phone with optional GSM module or to a control centre).
- **RS 485 interface** for connecting to PC-supported temperature documentation (using the optional PC-KIT).
- **Ventilation-enforced refrigerating machine**, vibration free, hermetically sealed, energy saving, low noise, easy to service. Inlet air and exhaust air flow through the ventilation slits at the front.

Specification

Capacity	170 litres
Temperature setting	-41 °C
Voltage	220 – 240 V, 50 Hz
Power consumption	460 watts
Normal consumption	5.9 kWh/24 h
Admissible ambient temperature	from +10 °C to +32 °C
Heat emission (max.)	500 watts
Exterior dimensions (including door handle and distance from wall)	w x d x h = 70 x 77 x 122 cm
Interior dimensions	w x d x h = 55 x 52 x 60 cm (usable width 3 cm, usable depth 15 cm, usable height 13 cm less)
Exterior dimensions with door open at 90°	w x d = 70 x 136 cm
Drawer inner dimensions	w x d x h = 52 x 32 x 10 cm
Max. load drawer	50 kg
Weight	Net weight 115 kg, gross weight 125 kg

Optional equipment

- **Equipped with castors.**
- **Drawer insert** (set) with 3 adjustable length and 21 cross dividers per drawer.
- **Additional length and cross dividers.**
- **GSM module** for alarm text message transmission.
- **Temperature documentation:**
 - PC-KIT-NET, PC-KIT-USB-MONITORING or PC-KIT-STICK including software for temperature documentation.
 - 4-pin PT 100 or PT 1000 temperature sensor, class 1/3 B, including built-in reference body.
 - Disc-type pen recording thermometer, with 7-day measuring cycle, incorporated, with 100 recording discs and 5 felt tip pens.